

HENKOVAC IMMERSION TANKS: FOR SHRINK PACKAGES

- > Full stainless steel immersion tanks for shrink packages
- > Immersion platform with rollers for easily loading and unloading
- > Automatic water level and temperature control
- > Wheels for added flexibility



SPECIFICATIONS IMMERSION TANKS

	WATER CONTENT	IMMERSION PLATFORM	IMMERSION DEPTH	DIMENSIONS (WxDxH)	STANDARD VOLTAGE*	POWER CONSUMPTION	WEIGHT
HV 40/60	70 Ltr	570 x 400	250	700 x 620 x 1550	400-3-50 Hz	9 kw	105 kg
HV 55/75	140 Ltr	730 x 535	250	1018 x 755 x 1550	400-3-50 Hz	15 kw	135 kg

Dimensions in mm *Machines can be supplied with all worldwide voltages applicable

CONVERSION TABLE OLD & NEW

	HENKOVAC NEW	HENKOVAC OLD
TRANSPARENT COVER & STAINLESS STEEL CHAMBER		
TABLE TOP	T2	MINI+MAXI
TABLE TOP	T3	GASTRO+100i
TABLE TOP	T4	GASTROPRO+150i+153
TABLE TOP	T5	163
TRANSPARENT COVER & STAINLESS STEEL CHAMBER		
MOBILE	M1	170i+193
MOBILE	M2	200i+253
MOBILE	M3	NEW: 163 MOBILE VERSION
STAINLESS STEEL COVER & FLAT WORKING SURFACE		
MOBILE	M4	203
MOBILE	M5	303
MOBILE	M6	303 XL
ALUMINUM COVER & CHAMBER		
MOBILE	M7	200
MOBILE	M8	300
DOUBLE CHAMBER	D1	403XL
DOUBLE CHAMBER	D3	453XL + 493XL
DOUBLE CHAMBER	D4	503XL
DOUBLE CHAMBER	D6	350
AUTOMATIC LINE	No changes	A5000
IMMERSION TANK	No changes	HV 50/75
IMMERSION TANK	No changes	HV 40/60
TRAY SEALER	No changes	TPS Mini
TRAY SEALER	No changes	TPS XL
TRAY SEALER	No changes	TPS 1000
TRAY SEALER	No changes	TPS 2000
THERMOFORMER	No changes	TH FLEX
THERMOFORMER	No changes	TH RIGID